

## INSTRUCTION FOR 26192

1. IN REMOVING PART FROM VEHICLE AND DISASSEMBLING PART CAREFULLY NOTE THE SEQUENCE OF PARTS AS REMOVED.
2. THIS IS IMPORTANT AS THIS KIT IS USED ON VARIOUS VEHICLES THE THE SEQUENCE OF ASSEMBLY VARIES FROM VEHICLE TO VEHICLE.
3. THE BALL SHOULD BE MEASURED AND MUST BE WITHIN .005 OF TRUE SPHERICAL. IF THE BALL CHECKS OUT OF ROUND BEYOND .005 IT MUST BE REPLACED AS IT WILL CAUSE BINDING AND MAY BE A SAFETY PROBLEM.
4. REASSEMBLE THE NEW PARTS INTO THE HOUSING MATCHING THE SEQUENCE AS REMOVED. GREASE EACH PART AS ASSEMBLED. TIGHTEN THE THREADED PLUG UNTIL THE SPRING BOTTOMS THEN BACK THE TREADED PLUG OFF 1/2 TURN AND CONTINUE TO BACK OFF THE PLUG UNTIL THE NEXT COTTER PIN HOLE ALIGNS WITH THE SLOT IN THE PLUG. INSTALL NEW COTTER PIN. GREASE ASSEMBLE.